

# High Power Modular Level 4 DCFC: 100, 150, 200 KW

Power Engine Cabinet Model:	L4T-100	L4T-150	L4T-200			
Power Rating	100 KW	150 KW	200 KW			
# of Power Engines	2	3	4			
Input Power	480VAC-3P@130A	480VAC-3P@200A	480VAC-3P@265A			
Input Power Breaker	3 phase x 175A	3 phase x 250A	3 phase x 300A			
Power stage Efficiency Rating	>94% (Full Load)					
Max. Out DC Current Up To 950VDC	125A	180A	240A			
Max. Out DC Current Up To 500VDC	250A	375A	500A			
Max. Output DC Voltage	50-950VDC					
Max # of Dispensers	2	2	2			
Dimension : Weight	42"W x 36"D x 82"H : 1300/1550/1800 lbs					
Dispenser Model:	L4D-350		L4D-200		L4D-50	
Max Power Rating	350kW	80kW	200kW	80kW	50kW	50kW
Connectors	SAE CCS1 (Liquid Cooled)	CHAdeMO	SAE CCS1	CHAdeMO	SAE CCS1	CHAdeMO
Network	OCPP 1.5/1.6, EVGateway Network					
Output Power	350KW max		200kW max		50kW max	
Input Power (Auxiliary)	120VAC		120VAC		120VAC	
Input Current (Auxiliary)	30A		15A		15A	
Dimension / Weight	22"W x 12"D x 97"H / 600 lbs.					
Environmental and Compliance (System)						
Ambient Condition	-30°C to +50°C, 95% humidity, 6000ft altitude. NEMA 3R					
Safety Compliance	ETL Listed for USA & Canada; Complies with UL 2594 UL 2231-1, UL2231-2, NEC Article 625					

## Standard

- Dynamic Power Allocation in 50KW increments
- System available in one or two Dispenser configuration
- Payment types: CC, RFID (OCPP Network Enabled)
- 15" Outdoor Color Display
- Connector Configuration:
  - SAE Combo CCS1 and CHAdeMO

## Optional

- ISO 15118:2014
- Customizable Backlit Acrylic Topper
- Apple & Android Pay (Based on network Provider)
- Connector Configuration:
  - Dual SAE Combo CCS1
  - Single CHAdeMO
  - Single SAE Combo CCS1



**BTCPOWER**  
WWW.BTCPower.COM

1719 S Grand Ave  
Santa Ana CA, 92705