



ELECTRIC VEHICLE CHARGING SYSTEM

Product Specifications

	July 75	July 225	July 600
ENERGY ENGINE			
Power Rating	75 kW	225 kW	600 kW
Number of Power Engines	1-4	3	8
Input Power	10-30 kW 240 1Ph/480 VAC	30-90 kW 240 1Ph/480 VAC	30-200 kW 480 VAC
Input Power FLA	40-100 A	40-100 A	250 A
Power Efficiency Rating	> 90%	> 90%	> 90%
Max Current @ 920VDC	N/A	170 A	170 A
Max Current @ 500VDC	155 A	340 A	340 A
Max DC Voltage	500 VDC	1000 VDC	1000 VDC
Max Number of Dispensers	4	2	8
Dimensions	198" x 178"	198" x 178"	198" x 178"
Weight	7400 lbs	7800 lbs	16100 lbs
JULE DISPENSER			
Connector Output Max	4	2	4
Max Current (CHAdeMO)	125 A	125 A	125 A
Max Current (CCS)	170 A	200 A	200 A
Max DC Voltage	500 VDC	1000 VDC	1000 VDC
Output Power	75 kW · 75 kW · 75 kW · 75 kW	75 kW · 150 kW	150 kW · 150 kW · 150 kW · 150 kW
Network	OCPP 1.6 J	OCPP 1.6 J	OCPP 1.6 J
Jule Charger Dimensions	44" x 11" x 90" (w x d x h)	44" x 11" x 90" (w x d x h)	44" x 11" x 90" (w x d x h)
Jule Charger Weight	300 lbs	300 lbs	300 lbs
ENVIRONMENTAL & COMPLIANCE			
Ambient Conditions	-40 °C to 50 °C (-40 to 86 °F), 95% humidity, 6000 ft altitude, NEMA 3R		
Safety Compliance	UL and ESA approved for USA and Canada. Complies with UL2202, UL2231, UL 9540, NFPA855, NEC Article 625, CSA 22.2 No 1.07, FCC Part 15 Class A		

Jule Energy is powered by



eCAMION Inc

450 Midwest Road
Toronto, Canada
M1P 3A9

+1 (416) 755-6460
www.ecamion.com

Standard:

- 7" Outdoor Ruggedized Colour Screen with Push Button Control
- SAE 1772 Combo CCS1 & CHAdeMO
- Payment Type: CC, QR Code
- ISO 15118 (mid 2021)

Optional:

- 12" Ruggedized Screen (available early 2021)
- Apple & Android Play
- Single SAE J1772 Combo CCS1
- Single CHAdeMO
- Additional grid services
- 300 amp CCS cable (available 2021)

